

LipuJet-P-OAP

Product information for the product group




ACO Product benefits

- Grease separator according to EN 1825 for installation inside frost-free rooms
- Manufactured of polyethylene in oval shape
- Two covers odour-proof Ø 450 mm
- Inlet and outlet Ø 200 mm (NS 15 – 25) or Ø 250 mm (NS 30)
- With two inspection windows for sludge and grease control
- With two high pressure spray heads for perfect inner body cleaning
- Disposal pump for maximum lift heights up to 18 meters with 10 m³/h disposal performance
- Control unit with presets and flexible adjustments (cleaning and filling times)
- Automatically operated disposal pump (3,7 kW) with shut-off valve, disposal connection Ø 75 mm with Storz-B coupling R 2½"
- Two automatically operated high pressure pumps (3,9 kW each) and connection high pressure spray heads (150 bar) for combined mixing of the content and cleaning of the tank
- Automatically operated filling device R ¾" via solenoid valve
- Two inspection windows with wiper
- Operating side left or right

Item Technical Data 3815.85.32

| Nominal capacity | Contents | | | Operation side |
|------------------|--------------------|---------------------|----------------|----------------|
| | Sludge trap [l] | Grease store [l] | Overall [l] | |
| NS 15 | 1580 | 630 | 2850 | Left-hand |


Dimensions



| Nominal capacity | Dimensions | | | | | | |
|------------------|------------|------------|------------|------------|------------|------------|------------|
| | L1 [mm] | H1 [mm] | H2 [mm] | H3 [mm] | H4 [mm] | W1 [mm] | W2 [mm] |
| NS 15 | 3210 | 2090 | 1640 | 1300 | 1230 | 1530 | 1260 |

Accessories

| | Description | Used with | Description | Item number |
|--|--------------------|-----------|------------------|-------------|
| | Inlet valve DN 200 | | ■ Weight: 8.4 kg | 0170.20.83 |

| | Description | Used with | Description | Item number |
|---|---|---|--|-------------------|
|  | Grease layer thickness measuring device | <ul style="list-style-type: none"> ■ LipuJet-P <ul style="list-style-type: none"> □ Oval NS 1 – 10 □ Round NS 2 – 20 ■ LipuJet-S <ul style="list-style-type: none"> □ Oval NS 1 – 10 □ Round NS 2 – 20 ■ LipuSmart-P <ul style="list-style-type: none"> □ Oval NS 1 – 10 | <ul style="list-style-type: none"> ■ For electronic measurement of layer of grease ■ Suitable for liquid and/or congealing grease ■ Measuring device with plug and used connecting cable, length: 3 m ■ With two voltage-free changeover contacts to display full warning (80 %) and advance warning of fill level (50 %) ■ With visual display of fill level ■ With heated probe rod to increase reliability of operation ■ Operating voltage: 230VAC/5 VA ■ Max consumption approx. 12 W ■ Weight: 2.8 kg | 3300.11.50 |
| | Connection box | | <ul style="list-style-type: none"> ■ Weight: 10 kg | 7601.80.24 |

You can find further accessories under → [/38158532](#)