

LipuJet-P-OAP

Product information for the product group



ACO Product benefits


- Grease separator according to EN 1825 for installation inside frost-free rooms
- Manufactured of polyethylene in oval shape
- Two covers odour-proof Ø 450 mm
- Inlet and outlet Ø 200 mm (NS 15 – 25) or Ø 250 mm (NS 30)
- Automatically operated disposal pump (3,7 kW) with shut-off valve, disposal connection Ø 75 mm with Storz-B coupling R 2½"
- Two automatically operated high pressure pumps (3,9 kW each) and connection high pressure spray heads (150 bar) for combined mixing of the content and cleaning of the tank
- Automatically operated filling device R ¾" via solenoid valve
- Two inspection windows with wiper
- Operating side left or right
- With two inspection windows for sludge and grease control
- With two high pressure spray heads for perfect inner body cleaning
- Disposal pump for maximum lift heights up to 18 meters with 10 m³/h disposal performance
- Control unit with presets and flexible adjustments (cleaning and filling times)

Item Technical Data 3815.85.42

Nominal capacity	Contents			Operation side
	Sludge trap [l]	Grease store [l]	Overall [l]	
NS 15	1580	630	2850	Right-hand

ACO eServices on the Internet:


Dimensions



Nominal capacity	Dimensions						
	L1 [mm]	H1 [mm]	H2 [mm]	H3 [mm]	H4 [mm]	W1 [mm]	W2 [mm]
NS 15	3210	2090	1640	1300	1230	1530	1260

Accessories

	Description	Used with	Description	Item number
	Inlet valve DN 200		<ul style="list-style-type: none"> Weight: 8.4 kg 	0170.20.83

	Description	Used with	Description	Item number
	<p>Grease layer thickness measuring device</p>	<ul style="list-style-type: none"> ■ LipuJet-P <ul style="list-style-type: none"> □ Oval NS 1 – 10 □ Round NS 2 – 20 ■ LipuJet-S <ul style="list-style-type: none"> □ Oval NS 1 – 10 □ Round NS 2 – 20 ■ LipuSmart-P <ul style="list-style-type: none"> □ Oval NS 1 – 10 	<ul style="list-style-type: none"> ■ For electronic measurement of layer of grease ■ Suitable for liquid and/or congealing grease ■ Measuring device with plug and used connecting cable, length: 3 m ■ With two voltage-free changeover contacts to display full warning (80 %) and advance warning of fill level (50 %) ■ With visual display of fill level ■ With heated probe rod to increase reliability of operation ■ Operating voltage: 230VAC/5 VA ■ Max consumption approx. 12 W ■ Weight: 2.8 kg 	<p>3300.11.50</p>
	<p>Connection box</p>		<ul style="list-style-type: none"> ■ Weight: 10 kg 	<p>7601.80.24</p>

You can find further accessories under → [/38158542](#)

ACO eServices on the Internet:

Item number: 3815.85.42
Version: 19.10.2018
Page 3 of 3