

LipuJet-P-RAP Extension stage 3

Product information for the product group




ACO Product benefits

- Easy to transport and fit thanks delivery of individual parts
 - Odour-free emptying, cleaning and filling
 - Pre- and post-cleaning times can be set individually
 - Hydromechanical high-pressure cleaning – only a cold-water connection required
 - Small delivery dimensions
 - Low weight
- Grease separator plant as per DIN EN 1825 and DIN 4040-100
 - For indoors installation – frost free
 - With integrated sludge trap
 - Operating side: right/left
 - Draining connection, fire hose quick coupling B 2½"
 - Suction and emptying sump with drain plug socket 1½"
 - Inspection window with wiper
- Automatic high-pressure internal cleaning with pump
 - Nominal pressure: 175 bar
 - Capacity: 13 l/min
 - Chopping, mixing, rinsing in one process
 - Standard control with group fault reporting
 - Disposal pump with free flow impeller
 - Motor power: 3.0 kW/2850 rpm
 - Delivery performance: 20 m³/h at 1 bar medium delivery head
 - Stop valve upstream of disposal pump
- Odour-proof maintenance opening, diameter: 350 mm
 - Filling device with magnetic valve (connection ¾") for automatic refilling
 - Electrical connector: 400 V/50 Hz/16 A/6,9 kW
 - System ACO Passavant
 - Building Supervisory Authority approval Z-54.1-491

Item Technical Data 3510.73.82





| Nominal capacity | Nominal width | Contents | | | Weight | | | Operation side |
|------------------|---------------|-------------|--------------|---------|--------|------|---------------------------|----------------|
| | | Sludge trap | Grease store | Overall | Empty | Full | Heaviest single component | |
| | | [l] | [l] | [l] | [kg] | [kg] | [kg] | |
| NS 10 | DN 150 | 1150 | 400 | 2450 | 393 | 2843 | 116 | Right-hand |

Dimensions



| Nominal capacity | Dimensions | | | | | | | | | | | | | |
|------------------|------------|------|------|------|------|------|------|------|------|------|------|------|------|-------------------|
| | L1 | L2 | L3 | L4 | L5 | L6 | H1 | H2 | H3 | H4 | H5 | D | D1 | Z/Anzahl Segmente |
| | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | |
| NS 10 | 1820 | 60 | 150 | 520 | 65 | 260 | 1600 | 1500 | 2050 | 2100 | 2300 | 160 | 1660 | 785/3 |

Accessories

| | Description | Used with | Description | Item number |
|---|---------------------|---|--|-------------------|
|  | Sampling pot DN 150 | <ul style="list-style-type: none"> ■ Grease separator LipuJet-P/LipuSmart-P <ul style="list-style-type: none"> □ NS 5.5 – 10 ■ Starch separator FapuJet-P-OAP <ul style="list-style-type: none"> □ NS 2 | <ul style="list-style-type: none"> ■ For installation of horizontal pipes DN 150 to grease separator ■ Round shape with <ul style="list-style-type: none"> □ Coupling socket seal (material SBR) on inlet and spigot on outflow □ Odour-proof maintenance opening DN 450 ■ Weight: 10.1 kg | 3300.09.21 |
|  | Sampling pot DN 150 | <ul style="list-style-type: none"> ■ Grease separator LipuJet-P/LipuSmart-P <ul style="list-style-type: none"> □ NS 5.5 – 10 ■ Starch separator FapuJet-P-OAP <ul style="list-style-type: none"> □ NS 2 | <ul style="list-style-type: none"> ■ For installation in vertical pipes DN 150 going to grease separator ■ Round shape with <ul style="list-style-type: none"> □ Coupling socket seal (material SBR) on inlet and spigot on outflow □ Odour-proof maintenance opening DN 450 ■ Weight: 10.1 kg | 3300.10.21 |
|  | Viewing window | <ul style="list-style-type: none"> ■ Grease separator <ul style="list-style-type: none"> □ LipuJet-P-OB/OD/R/RD □ LipuSmart-P-OB/OD ■ BioJet-P-OM/RM (NS 2-25) | <ul style="list-style-type: none"> ■ Nominal width: DN 200 ■ With screen wiper ■ Weight: 3.2 kg | 3300.11.10 |
|  | Filling device | <ul style="list-style-type: none"> ■ Grease separator <ul style="list-style-type: none"> □ LipuJet-P-OB/OD/R/RD □ LipuSmart-P-OB/OD ■ BioJet-P-OM/RM (NS 2-25) | <ul style="list-style-type: none"> ■ Free outlet as per DIN 1988 Part 4 ■ For connection to drinking water supply ■ With ball valve R 3/4" ■ With pressure relief valve ■ Weight: 3.5 kg | 3300.11.22 |

| | Description | Used with | Description | Item number |
|---|---|---|--|-------------------|
|  | Grease layer thickness measuring device | <ul style="list-style-type: none"> ■ LipuJet-P <ul style="list-style-type: none"> □ Oval NS 1 – 10 □ Round NS 2 – 20 ■ LipuJet-S <ul style="list-style-type: none"> □ Oval NS 1 – 10 □ Round NS 2 – 20 ■ LipuSmart-P <ul style="list-style-type: none"> □ Oval NS 1 – 10 | <ul style="list-style-type: none"> ■ For electronic measurement of layer of grease ■ Suitable for liquid and/or congealing grease ■ Measuring device with plug and used connecting cable, length: 3 m ■ With two voltage-free changeover contacts to display full warning (80 %) and advance warning of fill level (50 %) ■ With visual display of fill level ■ With heated probe rod to increase reliability of operation ■ Operating voltage: 230VAC/5 VA ■ Max consumption approx. 12 W ■ Weight: 2.8 kg | 3300.11.50 |

You can find further accessories under → </35107382>