

LipuJet-P-RB Basic type

Product information for the product group



ACO Product benefits


- Easy to transport and fit thanks delivery of individual parts
- Upgrade to levels 1 and 3 possible
- Small delivery dimensions
- Low weight

- Grease separator plant as per DIN EN 1825 and DIN 4040-100
- For indoors installation – frost free
- With integrated sludge trap
- Operating side: right/left
- Suction and emptying sump with drain plug socket 1½"
- Odour-proof maintenance opening, diameter: 350 mm
- System ACO Passavant
 - Building Supervisory Authority approval Z-54.1-491

Item Technical Data 3515.32.30

Nominal capacity	Nominal width	Contents			Weight		
		Sludge trap	Grease store	Overall	Empty	Full	Heaviest single component
		[l]	[l]	[l]	[kg]	[kg]	[kg]
NS 15	DN 200	1950	800	3610	357	3967	134





Dimensions



Nominal capacity	Dimensions									
	L1	L2	L3	H1	H2	H3	H4	D	D1	Z/Anzahl Segmente
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	
NS 15	2130	60	200	1765	1665	2200	2400	200	1920	880/3

Accessories

	Description	Used with	Description	Item number
	Sampling pot DN 200	<ul style="list-style-type: none"> Grease separator LipuJet-P <ul style="list-style-type: none"> NS 15 – 20 	<ul style="list-style-type: none"> For installation of horizontal pipes DN 200 to grease separator Round shape with <ul style="list-style-type: none"> Coupling socket seal (material SBR) on inlet and spigot on outflow Odour-proof maintenance opening DN 450 Weight: 10.3 kg 	3300.09.31

	Description	Used with	Description	Item number
	Sampling pot DN 200	<ul style="list-style-type: none"> ■ Grease separator LipuJet-P <ul style="list-style-type: none"> □ NS 15 – 20 	<ul style="list-style-type: none"> ■ For installation in vertical pipes DN 200 going to grease separator ■ Round shape with <ul style="list-style-type: none"> □ Coupling socket seal (material SBR) on inlet and spigot on outflow □ Odour-proof maintenance opening DN 450 ■ Weight: 10.2 kg 	3300.10.31
	Viewing window	<ul style="list-style-type: none"> ■ Grease separator <ul style="list-style-type: none"> □ LipuJet-P-OB/OD/R/RD □ LipuSmart-P-OB/OD ■ BioJet-P-OM/RM (NS 2-25) 	<ul style="list-style-type: none"> ■ Nominal width: DN 200 ■ With screen wiper ■ Weight: 3.2 kg 	3300.11.10
	Filling device	<ul style="list-style-type: none"> ■ Grease separator <ul style="list-style-type: none"> □ LipuJet-P-OB/OD/R/RD □ LipuSmart-P-OB/OD ■ BioJet-P-OM/RM (NS 2-25) 	<ul style="list-style-type: none"> ■ Free outlet as per DIN 1988 Part 4 ■ For connection to drinking water supply ■ With ball valve R ¾" ■ With pressure relief valve ■ Weight: 3.5 kg 	3300.11.22
	Grease layer thickness measuring device	<ul style="list-style-type: none"> ■ LipuJet-P <ul style="list-style-type: none"> □ Oval NS 1 – 10 □ Round NS 2 – 20 ■ LipuJet-S <ul style="list-style-type: none"> □ Oval NS 1 – 10 □ Round NS 2 – 20 ■ LipuSmart-P <ul style="list-style-type: none"> □ Oval NS 1 – 10 	<ul style="list-style-type: none"> ■ For electronic measurement of layer of grease ■ Suitable for liquid and/or congealing grease ■ Measuring device with plug and used connecting cable, length: 3 m ■ With two voltage-free changeover contacts to display full warning (80 %) and advance warning of fill level (50 %) ■ With visual display of fill level ■ With heated probe rod to increase reliability of operation ■ Operating voltage: 230VAC/5 VA ■ Max consumption approx. 12 W ■ Weight: 2.8 kg 	3300.11.50

You can find further accessories under → /35153230