

LipuMax-P-B

Product information for the product group



ACO Product benefits

- For gully top designs for load class D 400, shaft has buoyancy safety up to the upper side of the shaft manhole cover without need for on-site concrete castings.
- Proven stability: 50 years


- Grease separator plant as per DIN EN 1825 and DIN 4040-100
- For underground installation
- Emptying and cleaning via shaft manhole cover
- System ACO Passavant
- Building Supervisory Authority approval Z-54.1-509
- Suitable top sections
- Top sections

Item Technical Data 3205.80.10

Nominal capacity	Inlet/ Outlet	Contents			Weight
		Sludge trap [l]	Grease store [l]	Overall [l]	
NS 5.5	DN 150	1065	230	1960	107

ACO eServices on the Internet:


Dimensions



Nominal capacity	Sludge trap [l]	Dimensions		
		D [mm]	H [mm]	H1 [mm]
NS 5.5	1065	160	2611	2221

Accessories

	Description	Used with	Description	Item number
	Extension 450	<ul style="list-style-type: none"> Sampling shaft 	<ul style="list-style-type: none"> Made from plastic, material polyethylene For fitting on upstream shaft for deep installations Structure height: 100 – 650 mm (can be reduced to 45 mm by cutting off at cutting marks) Max. two extension can be used Weight: 8.8 kg 	3300.13.00

	Description	Used with	Description	Item number
	<p>Grease layer thickness measuring device</p>	<ul style="list-style-type: none"> Grease separator LipuMax-P for underground installation Stach separator FapuMax-P for underground installation 	<ul style="list-style-type: none"> For electronic measurement of layer of grease Suitable for liquid and/or congealing grease Measuring device with plug and used connecting cable, length: 3 m With two voltage-free changeover contacts to display full warning (100 %) and advance warning of fill level (80 %) With visual display of fill level for advance warning and full warning With heated probe rod to increase reliability of operation Operating voltage: 230 V/50 Hz Max consumption approx. 12 W 	
			Cable length: 10 mWeight: 6.4 kg	3300.11.70
			Cable length: 20 mWeight: 7.8 kg	3300.11.71
			Cable length: 30 mWeight: 9.6 kg	3300.11.72
	<p>Storage</p>	<ul style="list-style-type: none"> Grease separator LipuMax-P for underground installation Starch separator FapuMax-P for underground installation 	<ul style="list-style-type: none"> Made from concrete Diameter: 625 mm Thickness: 60 mm Without seal Displacement-proof Height <ul style="list-style-type: none"> 60 mm excluding mortar joints 70 mm including mortar joints Weight: 50 kg 	8700.20.00
	<p>Storage</p>	<ul style="list-style-type: none"> Grease separator LipuMax-P for underground installation Starch separator FapuMax-P for underground installation 	<ul style="list-style-type: none"> Made from concrete Diameter: 625 mm Thickness: 80 mm Without seal Displacement-proof Height <ul style="list-style-type: none"> 80 mm excluding mortar joints 90 mm including mortar joints Weight: 60 kg 	8700.20.10
	<p>Storage</p>	<ul style="list-style-type: none"> Grease separator LipuMax-P for underground installation Starch separator FapuMax-P for underground installation 	<ul style="list-style-type: none"> Made from concrete Diameter: 625 mm Thickness: 100 mm Without seal Displacement-proof Height <ul style="list-style-type: none"> 100 mm excluding mortar joints 110 mm including mortar joints Weight: 70 kg 	8700.20.20

You can find further accessories under → /32058010

