


Multi-Mini duo

Product information for the product group



ACO Product benefits


- Ready to connect
- Ergonomic carrying handles
- Different inlet heights can be selected
- High usable volume – up to 140 l
- All components with high chemical stability
- Suitable for installation downstream of grease separators up to NS 4
- Pump can be dismantled without tools
- Designed to fit through narrow doorways 700 mm
- Low weight

- Areas of application
 - Downstream of grease separators up to NS 4
 - Laundries
 - Rows of showers
 - Basement areas
- Polyethylene tank
 - Scour outlet R 1"
 - Service opening for simple maintenance, diameter: 340 mm
 - Fixing kit for attachment against floating
 - Connector for hand membrane pump DN 50
 - 4 horizontal intake sockets DN 100
 - 1 vertical inlet nozzle DN 100
 - Optionally 1 vertical inlet nozzle DN 50 (accessory)
 - 1 ventilation socket DN 70
- Connection pressure line
 - Special backflow stop with ball in housing
 - With venting and fixing screw
 - Connection: Rp 2"
- 2 grey water underwater pumps
 - With 3-phase submerged motor pump: 400 V, 50 Hz – Version D
 - With A.C. submerged motor pump: 230 V, 50 Hz – Version W
 - IP 68 protection
 - With blockage-free free flow impeller
 - 10 m mains cable
- Level switching
 - Pneumatic level switching with 10 m control lines
 - Optionally with air bubble injection for increased operational security when installing downstream of grease separators (accessory)
- Controls
 - IP 54 protection
 - 1.5 m cable and EEC plug (16 A) – version D
 - 1.5 m cable and safety plug (16 A) – version W
 - Mains-free group fault and operational messages
- Tested to DIN EN 12050-2


Item Technical Data 1206.00.04

Type	Motor power		Power consumption	Voltage	Rev count	Granulation	Usable volume			Total volume	Weight
	P1	P2					Inlet height Z1	Inlet height Z2	Top inlet		
	[kW]	[kW]					[l]	[l]	[l]		
Multi-Mini DWP 1.2	1.8	1.1	8.2	230	2900	50	55	100	130	195	74

Dimensions




Performance parameters



Type	Delivery head [m]	Delivery flow Q with overall delivery head H						Conveyance media temperature	
		2 m [l/s]	4 m [l/s]	6 m [l/s]	8 m [l/s]	10 m [l/s]	12 m [l/s]	Normal [°C]	Maximum [°C]
Muli-Mini DWP 1.2	2 – 12	10.3	8.7	7.0	5.4	3.6	1.8	40	65

Accessories

	Description	Used with	Description	Item number
	Inlet valve DN 100	<ul style="list-style-type: none"> Wastewater lifting plant Polyethylene grease separator Polyethylene starch separator Upstream tank plant <ul style="list-style-type: none"> Typ 2 and 4 LipuMobil-P – Type 0.5 	<ul style="list-style-type: none"> Made of PVC 110 mm push socket on both sides with rim sealing ring Overall dimensions: 176 x 330 mm (L x H) Weight: 3.1 kg 	0175.13.84
	Inlet valve DN 100		<ul style="list-style-type: none"> Weight: 5.9 kg 	0175.31.87

	Description	Used with	Description	Item number
	Inlet valve DN 50	<ul style="list-style-type: none"> ■ LipuMobil-P – Type 0,3 ■ Multi-Mini 	<ul style="list-style-type: none"> ■ Made of PVC ■ DN 50 ■ With sealing ring as per DIN EN 19538 ■ Weight: 0.4 kg 	0175.18.33
	Connection ports		<ul style="list-style-type: none"> ■ DN 50 ■ Duct Type A 40 x 50 x R 1¼" ■ Minimum height: 250 mm 	0175.09.27

You can find further accessories under → [/12060004](#)