


Channel body ACO ShowerDrain C, Horizontal Flange, Horizontal lateral outlet

Product information for the product group


ACO Product benefits

- Minimum installation height
- Meets requirements of all sound protection levels (SSt I-III in acc. with VDI 4100)
- Free access to the pipe for optimal cleaning
- Factory-welded hydro-shaped gully, guarantees permanent tightness
- Removable foul air trap for optimal cleaning
- High drainage capacity



- Material: Stainless steel, material grade 304
- Load class: K3
- Internal channel width: 64 mm
- Installation height: 92-140 mm (incl. 12 mm frame height)
- Flow rate:
 - 0.72 l/s (WS50 with 10 mm build-up)
 - 0.91 l/s (WS50 with 20 mm build-up as per EN 1253-1)
- Outlet socket: Suitable for all push-fit pipe socket systems
- Socket version: ND 50
- Foul air trap: 2-part, removable
- Type of flange: surrounding flange
- Channel body: Pickle passivated
- Mounting: Ready for installation
- Sound protection (as standard)
- Height adjustability: 48 respectively 74 mm using height-adjustable feet (to be ordered as an accessory)
- Grating variants: Stainless steel design gratings, tileable cover
- Supplementary components: ACO ShowerStep and ACO EasyStop

Item Technical Data



| Part No | Description | Odour trap | Dimensions | | |
|---------|--|------------|------------|------------|-----------------------|
| | | | L1 [mm] | L2 [mm] | Overall Width [mm] |
| 2131534 | Surrounding flange, socket horizontal/lateral | With | 585 | 645 | 130 |
| 2131535 | Surrounding flange, socket horizontal/lateral | With | 685 | 745 | 130 |
| 2131536 | Surrounding flange, socket horizontal/lateral | With | 785 | 845 | 130 |
| 2131537 | Surrounding flange, socket horizontal/lateral | With | 885 | 945 | 130 |
| 2131538 | Surrounding flange, socket horizontal/lateral | With | 985 | 1045 | 130 |
| 2131539 | Surrounding flange, socket horizontal/lateral | With | 1085 | 1145 | 130 |
| 2131540 | Surrounding flange, socket horizontal/lateral | With | 1185 | 1245 | 130 |