


Channel body ACO ShowerDrain E - Flexible Floor

Product information for the product group


ACO Product benefits

- Version for tile and flexible flooring
- Option for horizontal and vertical outlets
- Flexible for any installation situation
- Horizontal gully body can be rotated 360°



- Material: Stainless steel, material grade 304
- Gully Body: Plastic
- Load class: K3
- Internal channel width: 107 mm
- Installation height: 150-156 mm for flexible floors
- Flow rate:
 - 0.4 l/s (with 20 mm build-up as per EN 1253-1)
- Outlet socket: Suitable for all push-fit pipe socket systems
- Socket version: ND 50
- Foul air trap: 2-part, removable
- Type of flange: Surrounding
- Channel body: Electro-polished
- Mounting: Modular assembly system consisting of channel body, screwed gully body and design grating
- Grating variants: Stainless steel design gratings
- Supplementary components: ACO ShowerStep and ACO EasyStop

Item Technical Data

 Part No	Description	Odour trap	Dimensions		
			L1 [mm]	L2 [mm]	Overall Width [mm]
105781	360° Connector, Horizontal flange	With	700	760	170
105782	360° Connector, Horizontal flange	With	800	860	170
105783	360° Connector, Horizontal flange	With	900	960	170
105784	360° Connector, Horizontal flange	With	1000	1060	170
105785	360° Connector, Horizontal flange	With	1200	1260	170