


ACO ShowerDrain B

Product information for the product group


ACO Product benefits

- Minimum building height: 77 mm, unfinished floor level
- Full access to pipeline for optimum cleaning
- Stainless steel channel with screwed plastic gully,
- No risk of leakage
- Unique profile of grating reduces overshooting of water
- 2 in 1 spigot with ND 40 and ND 50
- Available with attached sealing sleeve



- Material:
 - Channel: Stainless steel, material grade 304
 - Gully: Plastic (ABS)
- Load class: K3
- Internal channel width: 64 mm
- Flow rate:
 - 0.35 l/s (without build-up)
 - 0.55 l/s (20 mm build-up as per EN1253-1)
- Outlet socket: Suitable for all push-fit pipe socket systems
- Socket version: ND 40/50
- Foul air trap: 1-piece with removable submersible pipe
- Flange design: Permanently cast-on, for optimum connection of a compound seal, alternatively with a sealing sleeve
- Type of flange: Surrounding
- Mounting: Ready for installation
- Total installation height:
 - 89 mm (with water trap 30 mm)
- Channel: Pickle passivated
- Grating: Grinded
- Grating variant: Design Slot included in scope of delivery
- Supplementary components: ACO ShowerStep, ACO Lightline Pro and different gully bodies

Item Technical Data



Part No	Description	Dimensions		
		L1 [mm]	L2 [mm]	Overall Width [mm]
3014005	Without sealing sleeve	685	745	130
3014042	Without sealing sleeve	785	845	130
3014043	Without sealing sleeve	885	945	130
3014044	Without sealing sleeve	985	1045	130