


Channel body ACO ShowerDrain C, Wall Flange, Horizontal outlet

Product information for the product group


ACO Product benefits

- Minimum installation height
- Meets requirements of all sound protection levels (SSt I-III in acc. with VDI 4100)
- Free access to the pipe for optimal cleaning
- Factory-welded hydro-shaped gully, guarantees permanent tightness
- Removable foul air trap for optimal cleaning
- High drainage capacity



- Material: Stainless steel, material grade 304
- Load class: K3
- Internal channel width: 64 mm
- Installation height: 92-140 mm (incl. 12 mm frame height)
- Flow rate:
 - 0.72 l/s (WS50 with 10 mm build-up)
 - 0.91 l/s (WS50 with 20 mm build-up as per EN 1253-1)
- Outlet socket: Suitable for all push-fit pipe socket systems
- Socket version: ND 50
- Foul air trap: 2-part, removable
- Type of flange: wall flange
- Channel body: Pickle passivated
- Mounting: Ready for installation
- Sound protection (as standard)
- Height adjustability: 48 respectively 74 mm using height-adjustable feet (to be ordered as an accessory)
- Grating variants: Stainless steel design gratings, tileable cover
- Supplementary components: ACO ShowerStep and ACO EasyStop

Item Technical Data



Part No	Description	Odour trap	Dimensions		
			L1 [mm]	L2 [mm]	Overall Width [mm]
2131391	Connector with socket and flange	With	585	645	116
2131392	Connector with socket and flange	With	685	745	116
2131393	Connector with socket and flange	With	785	845	116
2131394	Connector with socket and flange	With	885	945	116
2131395	Connector with socket and flange	With	985	1045	116
2131396	Connector with socket and flange	With	1085	1145	116
2131397	Connector with socket and flange	With	1185	1245	116