


Channel body ACO ShowerDrain C, Wall Flange, Horizontal lateral (left) outlet

Product information for the product group

ACO Product benefits

- Minimum installation height
- Meets requirements of all sound protection levels (SSt I-III in acc. with VDI 4100)
- Free access to the pipe for optimal cleaning
- Factory-welded hydro-shaped gully, guarantees permanent tightness
- Removable foul air trap for optimal cleaning
- High drainage capacity



- Material: Stainless steel, material grade 304
- Load class: K3
- Internal channel width: 64 mm
- Installation height: 92-140 mm (incl. 12 mm frame height)
- Flow rate:
 - 0.72 l/s (WS50 with 10 mm build-up)
 - 0.91 l/s (WS50 with 20 mm build-up as per EN 1253-1)
- Outlet socket: Suitable for all push-fit pipe socket systems
- Socket version: ND 50
- Foul air trap: 2-part, removable
- Type of flange: wall flange
- Channel body: Pickle passivated
- Mounting: Ready for installation
- Sound protection (as standard)
- Height adjustability: 48 respectively 74 mm using height-adjustable feet (to be ordered as an accessory)
- Grating variants: Stainless steel design gratings, tileable cover
- Supplementary components: ACO ShowerStep and ACO EasyStop

Item Technical Data



Part No	Description	Odour trap	Dimensions		
			L1 [mm]	L2 [mm]	Overall Width [mm]
2131548	Wall flange, horizontal/lateral left	With	585	645	116
2131550	Wall flange, horizontal/lateral left	With	685	745	116
2131552	Wall flange, horizontal/lateral left	With	785	845	116
2131554	Wall flange, horizontal/lateral left	With	885	945	116
2131556	Wall flange, horizontal/lateral left	With	985	1045	116
2131558	Wall flange, horizontal/lateral left	With	1085	1145	116
2131560	Wall flange, horizontal/lateral left	With	1185	1245	116